

**WAYNE**



YOUR SYMBOL OF CONFIDENCE

PRODUCT CATALOGUE **VOL 1**

**2020**





# WAYNE GUMBOOTS

With Wayne you get so much more than just a good pair of gumboots. They've gone the extra mile to ensure that you get world-class service as well as a quality product because at Wayne the customer is at the heart of everything they do.

Wayne's comfortable gumboots are engineered to provide hardwearing protection in diverse working conditions. Their range covers the constantly changing environments and hazards of agriculture and forestry, food processing and hygiene, heavy duty and general purpose applications.



# Contents

|  |                                                 |          |
|--|-------------------------------------------------|----------|
|  | Heavy Duty                                      | 06       |
|  | Food Processing & Hygiene<br>Polyurethane boots | 12<br>19 |
|  | Agriculture & Forestry                          | 20       |
|  | General Purpose Applications                    | 24       |
|  | Accessories                                     | 28       |

|                     |                                                               |  |
|---------------------|---------------------------------------------------------------|--|
| Safety features key |                                                               |  |
| STC                 | = With steel toe cap                                          |  |
| Without STC         | = Without steel toe cap                                       |  |
| Midsole             | = Steel midsole                                               |  |
| MOQ                 | = Please contact your KAM to discuss minimum order quantities |  |
| NP                  | = Non Penetration                                             |  |
|                     | = Made with recycled material                                 |  |

\* Wayne recommends all gumboots be worn with absorbent, cotton socks.



## Do you have time to be let down?

Of course you don't. Time is one commodity the working world is always short on. According to a survey done on working professionals in five countries, South Africans spend the most time at the office, with an average of 9.5 hour work days. That's a 47.5 hour work week. With statistics like that it's not surprising that as many as 88% of employees have a hard time juggling work and play. As a result, it's not uncommon to experience chronic fatigue and exhaustion in today's working culture.

With this in mind, Wayne understands that their customers need a company they can trust and rely on. A quality product alone is no longer good enough, it's the entire customer experience, from start to finish that really matters.

Wayne is dedicated to establishing strong relationships with their customers through an understanding of their individual needs, adopting a flexible approach and degree of personal contact. They've improved the areas of their business that are important to you, even the aspects you don't think about. It's these aspects that are often unnoticed, until something goes wrong.

Furthermore, Wayne have made selecting gumboots simpler than ever with a new user-friendly catalogue and website. With Wayne you get so much more than just a good pair of gumboots. Rest assured, they've taken care of almost everything, allowing you to concentrate on what you do best.

Wayne, your symbol of confidence.



YOUR SYMBOL OF CONFIDENCE

[www.wayne-safety.com](http://www.wayne-safety.com)



## So much more than just a good pair of gumboots

There is so much more to a good pair of gumboots than quality alone – but you're only going to notice that if something goes wrong. It's why we focus on those aspects you don't see, but truly value as a customer.





# Heavy Duty

Wayne's Heavy Duty gumboots provide comfortable and hardwearing protection for some of the toughest working environments. The range covers the high-risk industries of mining, construction and quarries.

Whether you are working above or below ground or simply manning heavy machinery on-site, the Heavy Duty range offers the suitable protection you need.



Made to Order: Please note that all MTO items for PVC gumboots require a minimum order quantity of 500 pairs, across a minimum of 5 sizes and will carry a lead time of 3 weeks production.



|       |       |       |
|-------|-------|-------|
| Upper | F1270 | F1310 |
| Sole  |       |       |

## Heavy Duty



### Egoli 1 - Knee Length Boots

PVC

|                                                          |               |    |
|----------------------------------------------------------|---------------|----|
| <b>F1260:</b> Black upper with toffee sole (Without STC) | SABS APPROVED | CE |
| <b>F1270:</b> Black upper with toffee sole (STC)         | SABS APPROVED | CE |
| <b>F1310:</b> Black upper with yellow sole (STC)         |               | CE |

- Features:
- PVC uppers for optimum flexibility and abrasion resistance
  - Available with or without a steel toe cap
  - Nitrile PVC sole for durability and protection against fats, oils and chemicals
  - The cleated sole design provides SRA level slip resistance and maximum soil release
  - Available with and without a steel midsole
  - Nylon liner allows for easy cleaning and quick drying for maximum hygiene
  - Optimal toe-spring for walking and kneeling

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue
  - Fur liner for warmth and comfort in cold environments

PVC Upper  
Nitrile PVC Sole  
Sizes: RSA 3 - 13

|      |   |   |          |   |   |          |   |      |   |   |   |       |   |   |   |
|------|---|---|----------|---|---|----------|---|------|---|---|---|-------|---|---|---|
| Heat | 2 | 1 | Abrasion | 2 | 1 | Chemical | * | Slip | 3 | 2 | 1 | Water | 3 | 2 | 1 |
|------|---|---|----------|---|---|----------|---|------|---|---|---|-------|---|---|---|

\* Please refer to the PVC chemical resistance table on page 31.



|       |       |       |       |       |
|-------|-------|-------|-------|-------|
| Upper | F1273 | F1283 | F1281 | F1285 |
| Sole  |       |       |       |       |

### Egoli 1 - Knee Length Boots

PVC

|                                                            |               |    |
|------------------------------------------------------------|---------------|----|
| <b>F1271:</b> White upper with white sole (STC)            | SABS APPROVED | CE |
| <b>F1273:</b> Yellow upper with black sole (STC)           | SABS APPROVED | CE |
| <b>F1281:</b> Black upper with toffee sole (STC & Midsole) |               | CE |
| <b>F1285:</b> Green upper with toffee sole (STC & Midsole) |               | CE |

- Features:
- Nitrile PVC uppers for optimum flexibility and abrasion resistance
  - Nitrile PVC sole for durability and protection against fats, oils and chemicals
  - The cleated sole design provides SRA level of slip resistance
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
  - Optimal toe-spring for walking and kneeling

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue
  - Fur liner for warmth and comfort in cold environments

Nitrile PVC Upper  
Nitrile PVC Sole  
Sizes: RSA 3 - 14\*\*

|      |   |   |          |   |   |          |   |      |   |   |   |       |   |   |   |
|------|---|---|----------|---|---|----------|---|------|---|---|---|-------|---|---|---|
| Heat | 2 | 1 | Abrasion | 2 | 1 | Chemical | * | Slip | 3 | 2 | 1 | Water | 3 | 2 | 1 |
|------|---|---|----------|---|---|----------|---|------|---|---|---|-------|---|---|---|

\* Please refer to the PVC chemical resistance table on page 31.

\*\* please note that size 14 is a different design to sizes 3-13, but carries the same accreditations





Egoli 2 - Metaguard

PVC

|                                                            |  |  |
|------------------------------------------------------------|--|--|
| <b>F1392:</b> Black upper with toffee sole (STC)           |  |  |
| <b>F1393:</b> Black upper with toffee sole (STC & Midsole) |  |  |

- Features:
- PVC uppers for optimum flexibility and abrasion resistance
  - Nitrile PVC sole for durability and protection against fats, oils and chemicals
  - Integrated metatarsal compliant to ISO 20345; 2011
  - The cleated sole design provides SRA level slip resistance and maximum soil release
  - Available with and without a steel midsole
  - Nylon liner allows for easy cleaning and quick drying for maximum hygiene
  - Optimal toe-spring for walking and kneeling

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue
  - Fur liner for warmth and comfort in cold environments

PVC Upper  
Nitrile PVC Sole  
Sizes: RSA 4 - 14



\* Recommended with PU insole for enhanced comfort.  
\* Please refer to the PVC chemical resistance table on page 31.

Egoli 2 - Knee Length Boots

PVC

|  |                                                            |  |  |
|--|------------------------------------------------------------|--|--|
|  | <b>F1360:</b> Black upper with toffee sole (Without STC)   |  |  |
|  | <b>F1370:</b> Black upper with toffee sole (STC)           |  |  |
|  | <b>F1380:</b> Black upper with toffee sole (STC & Midsole) |  |  |

- Features:
- PVC uppers for optimum flexibility and abrasion resistance
  - Nitrile PVC sole for durability and protection against fats, oils and chemicals
  - The cleated sole design provides SRA level of slip resistance
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
  - Optimal toe-spring for walking and kneeling

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue
  - Fur liner for warmth and comfort in cold environments
  - Recommended with a PU insole for enhanced comfort

PVC Upper  
Nitrile PVC Sole  
Sizes: RSA 5 - 14



\* Recommended with PU insole for enhanced comfort.  
\* Please refer to the PVC chemical resistance table on page 31.

|       |  |
|-------|--|
| Upper |  |
| Sole  |  |

|       |  |  |
|-------|--|--|
| Upper |  |  |
| Sole  |  |  |



Gripper

PVC

|                                                         |  |
|---------------------------------------------------------|--|
| <b>F1200:</b> Black upper with black sole (Without STC) |  |
| <b>F1210:</b> Black upper with black sole (STC)         |  |

- Features:
- Recycled PVC uppers for optimum flexibility and abrasion resistance
  - Available with or without steel toe cap
  - Recycled PVC sole for durability
  - The cleated sole design provides maximum slip resistance
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
  - Optimal toe-spring for walking and kneeling

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue
  - Fur liner for warmth and comfort in cold environments

Recycled PVC Upper  
Recycled PVC Sole  
Sizes: RSA 3 - 13



\* Please refer to the PVC chemical resistance table on page 31.

Ankle Miner

PVC

|  |                                                          |  |  |
|--|----------------------------------------------------------|--|--|
|  | <b>F1850:</b> Black upper with toffee sole (Without STC) |  |  |
|  | <b>F1860:</b> Black upper with toffee sole (STC)         |  |  |

- Features:
- PVC uppers for durability and abrasion resistance
  - Waterproof gusset preventing water penetration
  - Available with and without a steel toe cap
  - Nitrile PVC sole for durability and protection against fats, oils and chemicals
  - The cleated sole design provides slip resistance and maximum soil release
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
  - Optimal toe-spring for walking and kneeling

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue

PVC Upper  
Nitrile PVC Sole  
Sizes: RSA 5 - 12



\* Please refer to the PVC chemical resistance table on page 31.

|       |  |
|-------|--|
| Upper |  |
| Sole  |  |

|       |  |
|-------|--|
| Upper |  |
| Sole  |  |





Men's Chelsea HD

PVC

- F1506: Black upper with toffee sole (STC)
- F1507: Black upper with toffee sole (STC&Midsole)

- Features:
- PVC uppers for optimum flexibility and abrasion resistance
  - Nitrile PVC sole for durability and protection against fats, oils and chemicals
  - The cleated sole design provides SRA level slip resistance and maximum soil release
  - Elastic gusset
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
  - Optimal toe-spring for walking and kneeling
  - Comfortable heavy duty

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue

PVC Upper  
Nitrile PVC Sole  
Sizes: RSA 3 - 13

|      |                           |          |                           |          |              |      |                                        |       |                           |
|------|---------------------------|----------|---------------------------|----------|--------------|------|----------------------------------------|-------|---------------------------|
|      | <div>2</div> <div>1</div> |          | <div>2</div> <div>1</div> |          | <div>*</div> |      | <div>3</div> <div>2</div> <div>1</div> |       | <div>2</div> <div>1</div> |
| Heat |                           | Abrasion |                           | Chemical |              | Slip |                                        | Water |                           |

\* Please refer to the PVC chemical resistance table on page 31.



Men's Chelsea Gripper

PVC

- F1505: Black upper with black sole (STC)

- Features:
- Recycled PVC uppers for optimum flexibility and abrasion resistance
  - Recycled PVC sole for durability
  - The cleated sole design provides maximum slip resistance
  - Elastic gusset
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
  - Optimal toe-spring for walking and kneeling

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue

Recycled PVC Upper  
Recycled PVC Sole  
Sizes: RSA 3 - 13

|      |                           |          |                           |          |              |      |                                        |       |                           |
|------|---------------------------|----------|---------------------------|----------|--------------|------|----------------------------------------|-------|---------------------------|
|      | <div>2</div> <div>1</div> |          | <div>2</div> <div>1</div> |          | <div>*</div> |      | <div>3</div> <div>2</div> <div>1</div> |       | <div>2</div> <div>1</div> |
| Heat |                           | Abrasion |                           | Chemical |              | Slip |                                        | Water |                           |

\* Please refer to the PVC chemical resistance table on page 31.







# Food Processing & Hygiene

Wayne offer a reliable range of gumboots suitable for workers within the food processing and hygiene industries. This versatile range covers food processing, hygiene, cleaning and medical environments.

Available in industry relevant colours, the Food Processing and Hygiene range is easily cleaned, comfortable to wear and provides the necessary protection from workplace hazards such as fats, oils, blood and chemicals etc.



**Made to Order:** Please note that all MTO items for PVC gumboots require a minimum order quantity of 500 pairs, across a minimum of 5 sizes and will carry a lead time of 3 weeks production.



## Egoli 1 - Knee Length Boot

PVC

**F1271:** White upper with white sole (STC)



- Features:
- Nitrile PVC uppers for optimum flexibility and abrasion resistance
  - Nitrile PVC sole for durability and protection against fats, oils and chemicals
  - The cleated sole design provides SRA level of slip resistance
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
  - Optimal toe-spring for walking and kneeling

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue
  - Fur liner for warmth and comfort in cold environments

Nitrile PVC Upper  
Nitrile PVC Sole  
Sizes: RSA 3 - 14\*\*

|      |   |   |          |   |   |          |   |      |   |   |   |       |   |   |   |
|------|---|---|----------|---|---|----------|---|------|---|---|---|-------|---|---|---|
| Heat | 2 | 1 | Abrasion | 2 | 1 | Chemical | * | Slip | 3 | 2 | 1 | Water | 3 | 2 | 1 |
|------|---|---|----------|---|---|----------|---|------|---|---|---|-------|---|---|---|

\* Please refer to the PVC chemical resistance table on page 31.  
\*\* Please note that size 14 is a different design to sizes 3-13, but carries the same accreditations.



## Egoli 2 - Knee Length Boots

PVC

**F1302:** White upper with white sole (Without STC)



- Features:
- Nitrile PVC uppers for optimum flexibility and abrasion resistance
  - Nitrile PVC sole for durability and protection against fats, oils and chemicals
  - The cleated sole design provides SRA level of slip resistance
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
  - Optimal toe-spring for walking and kneeling

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue
  - Fur liner for warmth and comfort in cold environments

Nitrile PVC Upper  
Nitrile PVC Sole  
Sizes: RSA 5 - 14

|      |   |   |          |   |   |          |   |      |   |   |   |       |   |   |   |
|------|---|---|----------|---|---|----------|---|------|---|---|---|-------|---|---|---|
| Heat | 2 | 1 | Abrasion | 2 | 1 | Chemical | * | Slip | 3 | 2 | 1 | Water | 3 | 2 | 1 |
|------|---|---|----------|---|---|----------|---|------|---|---|---|-------|---|---|---|

\* Please refer to the PVC chemical resistance table on page 31.

|       |       |
|-------|-------|
| Upper | F1302 |
| Sole  |       |





Duralight Ladies 1

PVC

**F1689:** White upper with white sole (Without STC)

- Features:
- PVC uppers for optimum flexibility and abrasion resistance
  - PVC sole for durability and protection against blood, fats, oils and chemicals
  - Light in weight for enhanced comfort and reduced fatigue
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue

PVC Upper  
PVC Sole  
Sizes: RSA 3 -9

|      |   |          |   |          |   |      |   |       |   |
|------|---|----------|---|----------|---|------|---|-------|---|
|      | 2 |          | 2 |          | * |      | 2 |       | 3 |
| Heat | 1 | Abrasion | 1 | Chemical |   | Slip | 1 | Water | 1 |

\* Please refer to the PVC chemical resistance table on page 31.

|       |       |
|-------|-------|
| Upper | F1691 |
| Sole  |       |

Duralight Ladies 2

PVC

**F1681:** White upper with red sole (Without STC)

SABS APPROVED CE

**F1691:** White upper with white sole (Without STC)

- Features:
- Nitrile PVC uppers for optimum flexibility and abrasion resistance
  - Nitrile PVC sole for durability and protection against blood, fats, oils and chemicals
  - Light in weight for enhanced comfort and reduced fatigue
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue

Nitrile PVC Upper  
Nitrile PVC Sole  
Sizes: RSA 3 - 9

|      |   |          |   |          |   |      |   |       |   |
|------|---|----------|---|----------|---|------|---|-------|---|
|      | 2 |          | 2 |          | * |      | 2 |       | 3 |
| Heat | 1 | Abrasion | 1 | Chemical |   | Slip | 1 | Water | 1 |

\* Please refer to the PVC chemical resistance table on page 31.



Duralight Men's 2

PVC

**F1030:** White upper with red sole (Without STC)

SABS APPROVED CE

**F1020:** White upper with white sole (Without STC)

- Features:
- Nitrile PVC uppers for optimum flexibility and abrasion resistance
  - Nitrile PVC sole for durability and protection against blood, fats, oils and chemicals
  - Light in weight for enhanced comfort and reduced fatigue
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue
  - Fur liner for warmth and comfort in cold environments

Nitrile PVC Upper  
Nitrile PVC Sole  
Sizes: RSA 5 - 12

|      |   |          |   |          |   |      |   |       |   |
|------|---|----------|---|----------|---|------|---|-------|---|
|      | 2 |          | 2 |          | * |      | 2 |       | 3 |
| Heat | 1 | Abrasion | 1 | Chemical |   | Slip | 1 | Water | 1 |

\* Please refer to the PVC chemical resistance table on page 31.

|       |       |
|-------|-------|
| Upper | F1020 |
| Sole  |       |






**Duralight 1 Men's Chelsea** PVC

**F1504: Black upper with black sole (Without STC)** CE

- Features:
- Recycled PVC uppers for optimum flexibility and abrasion resistance
  - Recycled PVC sole for durability and protection against fats, oils and chemicals
  - The cleated sole design provides maximum slip resistance
  - Elastic gusset
  - Light in weight for enhanced comfort and reduced fatigue
  - Nylon liner allows for easy cleaning and quick drying for maximum hygiene

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue

Recycled PVC Upper  
Recycled PVC Sole  
Sizes: RSA 5 - 12

|                                                                                                                             |                                                                                                                                 |                                                                                                                     |                                                                                                                               |                                                                                                                                             |
|-----------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
|  <div>Heat</div> <div>2</div> <div>1</div> |  <div>Abrasion</div> <div>2</div> <div>1</div> |  <div>Chemical</div> <div>*</div> |  <div>Slip</div> <div>2</div> <div>1</div> |  <div>Water</div> <div>3</div> <div>2</div> <div>1</div> |
|-----------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|

\* Please refer to the PVC chemical resistance table on page 31.




**Duralight 2 Ladies Chelsea** PVC

**F1510: White upper with red sole (Without STC)**

- Features:
- Nitrile PVC uppers for optimum flexibility and abrasion resistance
  - Nitrile PVC sole for durability and protection against blood, fats, oils and chemicals
  - The cleated sole design provides maximum slip resistance
  - Light in weight for enhanced comfort and reduced fatigue
  - Elastic gusset
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene

- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue

Nitrile PVC Upper  
Nitrile PVC Sole  
Sizes: RSA 3 - 9

|                                                                                                                               |                                                                                                                                   |                                                                                                                       |                                                                                                                                 |                                                                                                                                               |
|-------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
|  <div>Heat</div> <div>2</div> <div>1</div> |  <div>Abrasion</div> <div>2</div> <div>1</div> |  <div>Chemical</div> <div>*</div> |  <div>Slip</div> <div>2</div> <div>1</div> |  <div>Water</div> <div>3</div> <div>2</div> <div>1</div> |
|-------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|

\* Please refer to the PVC chemical resistance table on page 31.







# THE DIFFERENCE BETWEEN PVC AND PU BOOTS

PVC gumboots are a popular choice because they are economical, dependable and provide protection against a wide range of acids, oils and chemicals. However, Wayne’s range of premium Polyurethane (PU) gumboots are fast becoming a contender within the market place - and with good reason.

Their range of PU gumboots can last up to 3 times longer than PVC boots, they are lighter in weight, thereby enhancing the comfort to the wearer.

Whilst the benefits of PVC gumboots are clear in many cases, PU gumboots do provide greater resistance to the harsher acids, oils and chemicals that are present in some industrial environments.

It is therefore recommended that customers consult the chemical resistance table provided at the back of this catalogue before making a final purchasing decision.



|       |       |       |       |       |       |
|-------|-------|-------|-------|-------|-------|
| Upper | P2010 | P2001 | P2011 | P2002 | P2012 |
| Sole  |       |       |       |       |       |
| Upper | P2020 | P2021 | P2022 | P2040 | P2041 |
| Sole  |       |       |       |       |       |

| Polyurethane Boots |                                                                       | PU     |
|--------------------|-----------------------------------------------------------------------|--------|
| P2000:             | White upper with blue sole (Without STC)<br>EN ISO and AS/NZS         | CE     |
| P2010:             | Olive green upper with grey sole (Without STC)<br>EN ISO and AS/NZS   | CE     |
| P2001:             | White upper with blue sole (STC)<br>EN ISO and AS/NZS                 | CE     |
| P2011:             | Olive green upper with grey sole (STC)<br>EN ISO and AS/NZS           | CE     |
| P2002:             | White upper with blue sole (STC & Midsole)<br>EN ISO and AS/NZS       | CE     |
| P2012:             | Olive green upper with grey sole (STC & Midsole)<br>EN ISO and AS/NZS | CE     |
| P2020:             | Black upper with grey sole (Without STC)<br>EN ISO, AS / NZS and ASTM | MOG CE |
| P2021:             | Black upper with grey sole (STC)<br>EN ISO, AS / NZS and ASTM         | MOG CE |
| P2022:             | Black upper with grey sole (STC / NP)<br>EN ISO, AS / NZS and ASTM    | MOG CE |
| P2040:             | Blue upper with blue sole (Without STC)<br>EN ISO, AS / NZS and ASTM  | MOG CE |
| P2041:             | Blue Upper with Blue sole (STC)<br>EN ISO, AS / NZS and ASTM          | MOG CE |

- Features:
- Significantly lighter in weight to enable enhanced comfort and reduce fatigue in order to increase productivity and safety
  - Directly enhanced thermal properties provide good insulation against heat and cold
  - Durability is expected to be 2 to 3 times longer than PVC as the material has excellent flex, cut and abrasion resistant qualities
  - The sole design ensures the highest possible SRC slip resistance rating
  - Boots are fitted with a Polyurethane footbed insole for enhanced comfort

Polyurethane (PU) Sole  
Polyurethane (PU) Upper

Sizes: RSA size 4 - 14

|             |             |          |             |          |   |      |             |       |        |
|-------------|-------------|----------|-------------|----------|---|------|-------------|-------|--------|
| Heat / Cold | 3<br>2<br>1 | Abrasion | 3<br>2<br>1 | Chemical | * | Slip | 3<br>2<br>1 | Water | 2<br>1 |
|-------------|-------------|----------|-------------|----------|---|------|-------------|-------|--------|

\* Please refer to the PU chemical resistance table on page 30.





# Agriculture & Forestry

Wayne offer a range of gumboots engineered for the varying hazards of the agriculture and forestry industries. From logger to farmer and heavy machinery driver, these gumboots provide the appropriate protection for wet and muddy conditions, allowing workers to focus on the job at hand with minimal distractions.



Made to Order: Please note that all MTO items for PVC gumboots require a minimum order quantity of 500 pairs, across a minimum of 5 sizes and will carry a lead time of 3 weeks production.



|       |       |       |       |
|-------|-------|-------|-------|
| Upper | F1671 | F1611 | F1689 |
| Sole  |       |       |       |



## Duralight Ladies 1

PVC

**F1661:** Black upper with black sole (Without STC)



**F1671:** Blue upper with white sole (Without STC)

**F1611:** Olive green upper with black sole (Without STC)



**F1689:** White upper with white sole (Without STC)

### Features:

- PVC uppers for optimum flexibility and abrasion resistance
- Durable PVC sole
- Light in weight for enhanced comfort and reduced fatigue
- Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene

### Optional Extras:

- Contour moulded cushion insole to enhance comfort and reduce fatigue

PVC Upper

PVC Sole

Sizes: RSA 3 - 9

|      |   |          |   |          |   |      |   |       |   |
|------|---|----------|---|----------|---|------|---|-------|---|
|      | 2 |          | 2 |          | * |      | 2 |       | 3 |
| Heat | 1 | Abrasion | 1 | Chemical |   | Slip | 1 | Water | 1 |

\* Please refer to the PVC chemical resistance table on page 31.

## Duralight Ladies 2

PVC

**F1681:** White upper with red sole (Without STC)



### Features:

- Nitrile PVC uppers for optimum flexibility and abrasion resistance
- Nitrile PVC sole for durability and protection against blood, fats, oils and chemicals
- Light in weight for enhanced comfort and reduced fatigue
- Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene

### Optional Extras:

- Contour moulded cushion insole to enhance comfort and reduce fatigue

Nitrile PVC Upper

Nitrile PVC Sole

Sizes: RSA 3 - 9

|      |   |          |   |          |   |      |   |       |   |
|------|---|----------|---|----------|---|------|---|-------|---|
|      | 2 |          | 2 |          | * |      | 2 |       | 3 |
| Heat | 1 | Abrasion | 1 | Chemical |   | Slip | 1 | Water | 1 |

\* Please refer to the PVC chemical resistance table on page 31.





Upper { F1090  
Sole {

## Duralight Men's 1

PVC

**F1040:** Black upper with black sole (Without STC)

CE

**F1090:** Green upper with black sole (Without STC)

CE

### Features:

- PVC uppers for optimum flexibility and abrasion resistance
- Durable PVC sole
- Light in weight for enhanced comfort and reduced fatigue
- Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene

### Optional Extras:

- Contour moulded cushion insole to enhance comfort and reduce fatigue
- Fur liner for warmth and comfort in cold environments

PVC Upper

PVC Sole

Sizes: RSA 5 - 12

|      |   |          |   |          |   |      |   |       |   |
|------|---|----------|---|----------|---|------|---|-------|---|
| Heat | 2 | Abrasion | 2 | Chemical | * | Slip | 2 | Water | 3 |
|      | 1 |          | 1 |          |   |      | 1 |       | 2 |
|      |   |          |   |          |   |      |   |       | 1 |

\* Please refer to the PVC chemical resistance table on page 31.



Upper { F1020  
Sole {

## Duralight Men's 2

PVC

**F1030:** White upper with red sole (Without STC)

SABS APPROVED CE

MTD

**F1020:** White upper with white sole (Without STC)

### Features:

- Nitrile PVC uppers for optimum flexibility and abrasion resistance
- Nitrile PVC sole for durability and protection against blood, fats, oils and chemicals
- Light in weight for enhanced comfort and reduced fatigue
- Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene

### Optional Extras:

- Contour moulded cushion insole to enhance comfort and reduce fatigue
- Fur liner for warmth and comfort in cold environments

Nitrile PVC Upper

Nitrile PVC Sole

Sizes: RSA 5 - 12

|      |   |          |   |          |   |      |   |       |   |
|------|---|----------|---|----------|---|------|---|-------|---|
| Heat | 2 | Abrasion | 2 | Chemical | * | Slip | 2 | Water | 3 |
|      | 1 |          | 1 |          |   |      | 1 |       | 2 |
|      |   |          |   |          |   |      |   |       | 1 |

\* Please refer to the PVC chemical resistance table on page 31.



Upper { F1270  
Sole {

## Egoli 1 - Knee Length Boots

PVC

**F1260:** Black upper with toffee sole (Without STC)

SABS APPROVED CE

**F1270:** Black upper with toffee sole (STC)

SABS APPROVED CE

### Features:

- PVC uppers for optimum flexibility and abrasion resistance
- Nitrile PVC sole for durability and protection against fats, oils and chemicals
- Available with or without a steel toe cap
- The cleated sole design provides SRA level slip resistance and maximum soil release
- Available with and without a steel midsole
- Nylon liner allows for easy cleaning and quick drying for maximum hygiene
- Optimal toe-spring for walking and kneeling

### Optional Extras:

- Contour moulded cushion insole to enhance comfort and reduce fatigue
- Fur liner for warmth and comfort in cold environments

PVC Upper

Nitrile PVC Sole

Sizes: RSA 3 - 13

|      |   |          |   |          |   |      |   |       |   |
|------|---|----------|---|----------|---|------|---|-------|---|
| Heat | 2 | Abrasion | 2 | Chemical | * | Slip | 3 | Water | 3 |
|      | 1 |          | 1 |          |   |      | 2 |       | 2 |
|      |   |          |   |          |   |      | 1 |       | 1 |

\* Please refer to the PVC chemical resistance table on page 31.



Upper { F1210  
Sole {

## Gripper

PVC

**F1200:** Black upper with black sole (Without STC)

CE

**F1210:** Black upper with black sole (STC)

CE

### Features:

- Recycled PVC uppers for optimum flexibility and abrasion resistance
- Recycled PVC sole for durability
- Available with or without steel toe cap
- The cleated sole design provides maximum slip resistance
- Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
- Optimal toe-spring for walking and kneeling

### Optional Extras:

- Contour moulded cushion insole to enhance comfort and reduce fatigue
- Fur liner for warmth and comfort in cold environments

Recycled PVC Upper

Recycled PVC Sole

Sizes: RSA 3 - 13

|      |   |          |   |          |   |      |   |       |   |
|------|---|----------|---|----------|---|------|---|-------|---|
| Heat | 2 | Abrasion | 2 | Chemical | * | Slip | 3 | Water | 3 |
|      | 1 |          | 1 |          |   |      | 2 |       | 2 |
|      |   |          |   |          |   |      | 1 |       | 1 |

\* Please refer to the PVC chemical resistance table on page 31.





# General Purpose Applications

This range is suitable for domestic, leisure, light industry and manufacturing applications, the range provides lightweight protection in wet and muddy conditions.

D  
Domestic

L  
Leisure

Lia  
Light industry applications

M  
Manufacturing



Made to Order: Please note that all MTO items for PVC gumboots require a minimum order quantity of 500 pairs, across a minimum of 5 sizes and will carry a lead time of 3 weeks production.



|       |       |       |       |
|-------|-------|-------|-------|
| Upper | F1661 | F1671 | F1689 |
| Sole  |       |       |       |



|       |       |       |
|-------|-------|-------|
| Upper | F1040 | F1090 |
| Sole  |       |       |

## Duralight Ladies 1

PVC

|        |                                           |  |
|--------|-------------------------------------------|--|
| F1611: | Olive upper with black sole (Without STC) |  |
| F1661: | Black upper with black sole (Without STC) |  |
| F1671: | Blue upper with white sole (Without STC)  |  |
| F1689: | White upper with white sole (Without STC) |  |

- Features:
- PVC uppers for optimum flexibility and abrasion resistance
  - Durable PVC sole
  - Light in weight for enhanced comfort and reduced fatigue
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue

PVC Upper  
PVC Sole  
Sizes: RSA 3 - 9

|      |   |          |   |          |   |      |   |       |   |
|------|---|----------|---|----------|---|------|---|-------|---|
| Heat | 2 | Abrasion | 2 | Chemical | * | Slip | 2 | Water | 3 |
|      | 1 |          | 1 |          |   |      | 1 |       | 2 |

\* Please refer to the PVC chemical resistance table on page 31.

## Duralight Men's 1

PVC

|        |                                                 |  |
|--------|-------------------------------------------------|--|
| F1010: | Black upper with ivory sole (Without STC)       |  |
| F1040: | Black upper with black sole (Without STC)       |  |
| F1090: | Olive green upper with black sole (Without STC) |  |

- Features:
- PVC uppers for optimum flexibility and abrasion resistance
  - Durable PVC sole
  - Light in weight for enhanced comfort and reduced fatigue
  - Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
- Optional Extras:
- Contour moulded cushion insole to enhance comfort and reduce fatigue
  - Fur liner for warmth and comfort in cold environments

PVC Upper  
PVC Sole  
Sizes: RSA 5 - 12

|      |   |          |   |          |   |      |   |       |   |
|------|---|----------|---|----------|---|------|---|-------|---|
| Heat | 2 | Abrasion | 2 | Chemical | * | Slip | 2 | Water | 3 |
|      | 1 |          | 1 |          |   |      | 1 |       | 2 |

\* Please refer to the PVC chemical resistance table on page 31.





|       |       |       |
|-------|-------|-------|
| Upper | F1270 | F1310 |
| Sole  |       |       |

## Egoli 1 - Knee Length Boots

PVC

|                                                          |               |    |
|----------------------------------------------------------|---------------|----|
| <b>F1260:</b> Black upper with toffee sole (Without STC) | SABS APPROVED | CE |
| <b>F1270:</b> Black upper with toffee sole (STC)         | SABS APPROVED | CE |
| <b>F1310:</b> Black upper with yellow sole (STC)         |               | CE |

### Features:

- PVC uppers for optimum flexibility and abrasion resistance
- Nitrile PVC sole for durability and protection against fats, oils and chemicals
- Available with or without a steel toe cap
- The cleated sole design provides SRA level slip resistance and maximum soil release
- Nylon liner allows for easy cleaning and quick drying for maximum hygiene
- Optimal toe-spring for walking and kneeling

### Optional Extras:

- Contour moulded cushion insole to enhance comfort and reduce fatigue
- Fur liner for warmth and comfort in cold environments

PVC Upper

Nitrile PVC Sole

Sizes: RSA 3 - 13

|      |   |   |          |   |   |          |   |      |   |   |   |       |   |   |   |
|------|---|---|----------|---|---|----------|---|------|---|---|---|-------|---|---|---|
| Heat | 2 | 1 | Abrasion | 2 | 1 | Chemical | * | Slip | 3 | 2 | 1 | Water | 3 | 2 | 1 |
|------|---|---|----------|---|---|----------|---|------|---|---|---|-------|---|---|---|

\* Please refer to the PVC chemical resistance table on page 31.

## Men's Chelsea Gripper

PVC

|                                                 |  |
|-------------------------------------------------|--|
| <b>F1505:</b> Black upper with black sole (STC) |  |
|-------------------------------------------------|--|

### Features:

- Recycled PVC uppers for optimum flexibility and abrasion resistance
- Recycled PVC sole for durability
- The cleated sole design provides maximum slip resistance
- Elastic gusset
- Nylon liner allows for easy cleaning and quick drying resulting in maximum hygiene
- Optimal toe-spring for walking and kneeling

### Optional Extras:

- Contour moulded cushion insole to enhance comfort and reduce fatigue

Recycled PVC Upper

Recycled PVC Sole

Sizes: RSA 3 - 13

|      |   |   |          |   |   |          |   |      |   |   |   |       |   |   |   |
|------|---|---|----------|---|---|----------|---|------|---|---|---|-------|---|---|---|
| Heat | 2 | 1 | Abrasion | 2 | 1 | Chemical | * | Slip | 3 | 2 | 1 | Water | 3 | 2 | 1 |
|------|---|---|----------|---|---|----------|---|------|---|---|---|-------|---|---|---|

\* Please refer to the PVC chemical resistance table on page 31.



## Duralight 2 Men's Chelsea

PVC

**F1503:** White upper with red sole (Without STC)

### Features:

- Nitrile PVC uppers for optimum flexibility and abrasion resistance
- Nitrile PVC sole for durability and protection against fats, oils and chemicals
- The cleated sole design provides maximum slip resistance
- Elastic gusset
- Light in weight for enhanced comfort and reduced fatigue
- Nylon liner allows for easy cleaning and quick drying for maximum hygiene

### Optional Extras:

- Contour moulded cushion insole to enhance comfort and reduce fatigue

Nitrile PVC Upper

Nitrile PVC Sole

Sizes: RSA 5 - 12

|      |   |   |          |   |   |          |   |      |   |   |       |   |   |   |
|------|---|---|----------|---|---|----------|---|------|---|---|-------|---|---|---|
| Heat | 2 | 1 | Abrasion | 2 | 1 | Chemical | * | Slip | 2 | 1 | Water | 3 | 2 | 1 |
|------|---|---|----------|---|---|----------|---|------|---|---|-------|---|---|---|

\* Please refer to the PVC chemical resistance table on page 31.





### Poron Pad Insole

Fitted as standard in Metaguard boots.

Sizes: RSA 5 -12



### Polyurethane Comfort Insole

Fitted as standard in all Polyurethane boots.

Sizes: RSA 4 -14



### Energiser Woollen Insole

The Energiser Woollen Insole is made from highly absorbent wool and treated with an Ultra-Fresh DM-25-WP process. This has the advantage of fighting fungal and bacterial infections while minimising conditions such as Athlete's Foot.

Sizes: RSA 5 -12



### Boot Fur Liner

For added comfort and warmth in cold environments.




### Chest Waders





PU


## CHEMICAL RESISTANCE TABLE FOR PU GUMBOOTS




Dissolves




Poor  
more than 30% change



Fair  
16 - 30% change



Good  
4 - 15% change



Excellent  
0.3% change

|                                 |   |                                      |   |                                   |   |
|---------------------------------|---|--------------------------------------|---|-----------------------------------|---|
| Acetic Acid 3 n                 | 3 | Diesel Oil                           | 5 | Methyl Glycol                     | 2 |
| Acetone                         | 2 | Dimethyl Acetamide                   | 1 | Methyl Glycol Acetate             | 2 |
| Aluminium Chloride 10% Sol.     | 4 | Dimethyl Formamide                   | 1 | Methylene Chloride                | 2 |
| Ammonia 3 n                     | 5 | Distilled Water                      | 5 | Mineral Oil                       | 5 |
| Ammonium Chloride 10% Sol.      | 5 | Ethanol                              | 3 | Nitric Acid 3 n                   | 1 |
| Aniline                         | 2 | Ether                                | 3 | N-Methyl Pyrrolidone              | 1 |
| ASTM-Fuel A                     | 2 | Ethyl Acetate                        | 2 | Ozone                             | 5 |
| ASTM-Fuel B                     | 4 | Ethylene Chloride                    | 3 | Paraffin Oil                      | 5 |
| ASTM-Fuel C                     | 3 | Ferric Chloride 10% Sol.             | 4 | Perchloroethylene                 | 2 |
| ASTM-Oil 1                      | 5 | Formic Acid 3 n                      | 2 | Petroleum                         | 5 |
| ASTM-Oil 2                      | 5 | Freon 12                             | 3 | Petroleum Ether                   | 5 |
| ASTM-Oil 3                      | 5 | Freon 22                             | 3 | Phosphoric Acid 3 n               | 3 |
| Benzene                         | 2 | Gear Box Oil SAE 90                  | 5 | Potassium Chloride 10% & 40% Sol. | 5 |
| Benzyl Alcohol                  | 1 | Glycerine                            | 5 | Potassium Dichromate 10% Sol.     | 5 |
| Bleach                          | 5 | Glycol                               | 5 | Potassium Hydroxide 3 n           | 5 |
| Brake Fluid ATE                 | 5 | Hydrochloric Acid 3 n                | 5 | Potassium Nitrate                 | 4 |
| Brake Fluid ATS                 | 5 | Hydrogen Peroxide 3%                 | 5 | Potassium Permanganate 5% Sol.    | 2 |
| Butane                          | 4 | Iso-Octane Fuel 1                    | 5 | Propane                           | 4 |
| Butyl Acetate                   | 2 | Iso-Octane 70%: 30% Toluene = Fuel 2 | 4 | Pyridine                          | 1 |
| Butyl Alcohol                   | 3 | Iso-Octane 50%: 50% Toluene = Fuel 3 | 3 | Sea Water (Technical)             | 5 |
| Calcium Chloride 10% & 40% Sol. | 5 | Iso-Propanol                         | 4 | Sodium Bisulphate 10% Sol.        | 4 |
| Carbon Disulphide               | 3 | Kerosine                             | 5 | Sodium Chloride 10% Sol.          | 5 |
| Carbon Tetrachloride            | 2 | Lactic Acid 3 n                      | 1 | Sodium Hypochlorite Sol. PH 13.3  | 3 |
| Caustic Soda Sol. 10%           | 5 | Lubricating Grease: Calcium based    | 5 | Sodium Sulphite                   | 4 |
| Chlorobenzene                   | 2 | : Lithium based                      | 5 | Sulphuric Acid 3 n                | 1 |
| Chloroform                      | 2 | : Sodium based                       | 5 | Terpentine (Pine Oil)             | 4 |
| Chromic Acid 3 n                | 2 | Magnesium Chloride 10% & 30% Sol.    | 5 | Tetrachlorethylene                | 2 |
| Citronic Acid 3 n               | 4 | Methane                              | 4 | Tetrahydrofuran                   | 2 |
| Cyclohexane                     | 4 | Methanol                             | 4 | Toluene                           | 2 |
| Cyclohexanon                    | 2 | Methyl Acetate                       | 2 | Trichloroethylene                 | 2 |
| Decalin                         | 3 | Methyl Ethyl Ketone 2                | 2 | Xylene                            | 2 |

If you are exposed to any of the acids, oils or chemicals that rate 1, 2 or 3 on the table we recommend a PVC gumboot.

The above table should be used as a general guide only. Performance in the actual working environment will depend upon the following: temperature of chemicals, concentrations of chemicals and duration of exposure.



PVC

## CHEMICAL RESISTANCE TABLE FOR PVC GUMBOOTS

|                         |   |                       |   |                        |   |                          |   |
|-------------------------|---|-----------------------|---|------------------------|---|--------------------------|---|
| Ace Tophenone           | 1 | Trithanol Amine       | 3 | Tetrahydrofuran        | 1 | Nitric Acid Concentrate  | 1 |
| Acetaldehyde            | 2 | Tung Oil              | 2 | Toluene                | 2 | Nitric Acid Red Fuming   | 1 |
| Acetates                | 1 | Turbine Oil           | 1 | Toluene                | 1 | Nitric Acid White Fuming | 1 |
| Acetic Acid             | 3 | Turpentine            | 2 | Toluene Di-Isocyanate  | 1 | Nitrobenzine             | 1 |
| Acetic Anhydride        | 2 | Citric Acid           | 2 | Trichlorethylene       | 1 | Nitromethane             | 1 |
| Acetone                 | 1 | Copper Chloride       | 3 | Trinitrolouene         | 2 | Nitropropane 95.5%       | 1 |
| Acrylonitrile           | 1 | Cottonseed Oil        | 3 | Vegetable Oil          | 2 | Octyl Alcohol            | 2 |
| Alcohols                | 2 | Cresols               | 2 | Vinegar                | 2 | Oleic Acid               | 2 |
| Aluminium Chloride      | 3 | Cutting Oil           | 2 | Water                  | 3 | Olive Oil                | 2 |
| Ammonium Carbonate      | 1 | Cyclohexanol          | 2 | Whisky                 | 2 | Oxalic Acid              | 3 |
| Ammonium Chloride       | 3 | Cyclohexane           | 2 | Xylene                 | 1 | Oxalic Acid              | 2 |
| Ammonium Fluoride       | 3 | Diacetone Alcohol     | 1 | Zinc Chloride          | 2 | Paint Remover            | 1 |
| Ammonium Hydroxide      | 3 | Diesel Oil            | 3 | Hydrofluoric Acid 48%  | 2 | PCBs                     | 1 |
| Ammonium Sulphate       | 3 | Diethylamine          | 2 | Hydrofluoric Acid 48%  | 1 | Pentane                  | 1 |
| Amyl Acetate            | 1 | Di-isobutyl Ketone    | 1 | Hydrogen Gas           | 3 | Perchlorethylene         | 1 |
| Aniline                 | 1 | Di-Isocyanate         | 2 | Hydrogen Peroxide 30%  | 2 | Perchloric Acid          | 1 |
| Animal Fats             | 3 | Dimethyl Aulphoxide   | 2 | Hydrogen Sulphide      | 2 | Petroleum Oils           | 3 |
| Aqua Regia              | 3 | Dimethyl Formamide    | 1 | Hydroquinone           | 2 | Peuta                    | 3 |
| Asphalt                 | 1 | Dioxane               | 1 | Iso Octane             | 3 | Phenol                   | 3 |
| Benzaldehyde            | 1 | Dyestuff              | 3 | Iso Octane             | 1 | Phenol                   | 1 |
| Benzine                 | 2 | Electroless Copper    | 3 | Isobutyl Alcohol       | 3 | Phosphoric Acid          | 2 |
| Bromine                 | 2 | Epoxy Resins          | 3 | Isopropyl Alcohol      | 3 | Pickling Solution        | 3 |
| Butane                  | 2 | Ethers                | 2 | Kerosene               | 2 | Pine Oil                 | 2 |
| Butane Liquid           | 3 | Ethyl Alcohol         | 3 | Lactic Acid            | 3 | Potassium Chloride       | 3 |
| Butyl Acetate           | 1 | Ethyl Cellulose       | 2 | Laquer Thinners        | 2 | Printing Ink             | 2 |
| Butyl Alcohol           | 3 | Ethyl Chloride        | 1 | Lauric Acid 36% EtOH   | 2 | Propane                  | 3 |
| Butyraldehyde           | 3 | Ethyl Ether           | 1 | Linoleic Acid          | 3 | Propane                  | 2 |
| Calcium Chloride        | 3 | Ethyl Formate         | 1 | Linseed Oil            | 2 | Propyl Acetate           | 2 |
| Calcium Hypochlorite    | 2 | Ethyle Acetate        | 1 | Lubricating Oils       | 3 | Propyl Alcohol           | 3 |
| Calcium Nitrate         | 3 | Ethylene Dichloride   | 1 | M.E.K.                 | 1 | Silicon Etch             | 2 |
| Carbon Disulphide       | 1 | Ethylene Glycol       | 3 | Methyl Bromide         | 1 | Skydrol 500              | 1 |
| Carbon Tetrachloride    | 2 | Ferric Chloride       | 3 | Methyl Chloride        | 2 | Sodium Chloride          | 3 |
| Carbon Tetrachloride    | 1 | Ferric Sulphate       | 3 | Methyl Isobutyl Ketone | 2 | Sodium Cyanide           | 3 |
| Castor Oil              | 3 | Formaldehyde          | 3 | Methyl Methacrylate    | 2 | Sodium Hydroxide         | 2 |
| Castor Oil              | 2 | Formic Acid           | 2 | Methylamine            | 2 | Sodium Hydroxide < 50%   | 3 |
| Cellosole Acetate       | 2 | Freon TF              | 1 | Methylene Chloride     | 1 | Sodium Peroxide          | 2 |
| Chloride                | 2 | Freons (except 22)    | 3 | Mineral Oil            | 2 | Stoddard Solvent         | 2 |
| Chlorine                | 2 | Furfural              | 1 | Mineral Oils           | 3 | Styrene                  | 1 |
| Chlorobenzine           | 1 | Gasoline              | 3 | Mineral Spirits        | 2 | Sulphur Dioxide          | 2 |
| Chloroform              | 1 | Gasoline              | 1 | Monoethanolamine       | 3 | Sulphuric Acid 95%       | 2 |
| Chloronaphthalene       | 1 | Glycerol              | 3 | Muriatic Acid          | 3 | Sulphuric Acid Fuming    | 1 |
| Chlorothene VG          | 1 | Hydraulic Fluid-Ester | 1 | Naptha                 | 1 | Sulpur Chloride          | 2 |
| Chrome Plating Solution | 3 | Hydraulic Oils        | 3 | Natural Gas            | 3 | Synthetic Oils           | 3 |
| Chromic Acid            | 1 | Hydrochloric Acid 38% | 3 | Nitric Acid (10%)      | 3 | Tannic Acid 65%          | 3 |
| Citric Acid             | 3 | Hydrocyanic Acid      | 2 | Nitric Acid 70%        | 2 |                          |   |

1 Dissolves 2 Fair 16 - 30% change 3 Excellent 0.3% change

The above table should be used as a general guide only. Performance in the actual working environment will depend upon the following: temperature of chemicals, concentrations of chemicals and duration of exposure.





**Phone:** +27 31 710 0400

**Fax:** +27 31 700 2607

**Email:** [info@bbfsafety.com](mailto:info@bbfsafety.com)

**Web:** [www.wayne-safety.com](http://www.wayne-safety.com)

40 Gillitts Road  
Pinetown  
3610  
South Africa

PO Box 1525  
Florida  
Gauteng  
1710  
South Africa



YOUR SYMBOL OF CONFIDENCE

